


Laser Measuring Device LLB-60-D (H)

Eglshalde 6
D-78647 Trossingen
Tel. +49 - (0) 74 25 / 228 - 0
Fax +49 - (0) 74 25 / 228 - 33
<http://www.tr-electronic.de>
Germany



- **Analog interface: 0...20 mA or 4...20 mA**
- **RS232 -, RS422 - interface**
- **Detection of positions**
- **Non contact distance measurement**
- **Distance measurements on**
 - natural surfaces : 0.05 up to approx. 65 m
 - reflective target plate : 0.05 up to approx. 500 m
- **LLB60-00600, LLB60-00601: without heating**
- **LLB60-00610, LLB60-00611: with heating**
- **Programmable**

Characteristics

Supply voltage.....	9...30 VDC
with heating.....	24...30 VDC
Current consumption without load	< 0.5 A
with heating.....	< 2.5 A
Measuring range	
on natural surfaces	typically 0.05...65 m
on reflective target plate	typically 0.05...500 m
Smallest unit displayed	0.1 mm
Measuring accuracy	
LLB60-00600, LLB60-00610.....	typically ± 1.5 mm at 2σ
LLB60-00601, LLB60-00611.....	typically ± 3.0 mm at 2σ
Time for a measurement	
Single measurement.....	typically 0.15...4 s
Tracking Mode.....	typically 0.15...4 s
Light source.....	Laser diode, red light
Wavelength λ	620...690 nm
Laser protection class.....	2 accor. IEC 60 825-1: 2001 / FDA 21CFR 1040.10 und 1040.11
Beam divergence.....	0.16 x 0.6 mrad
Pulse duration.....	0.45×10^{-9} s
Radiant power.....	< 0.95 mW
Life time	> 50.000 h at 20 °C
Analog interface ¹⁾	0...20 mA, 4...20 mA, $\leq 500 \Omega$
Configuration interfaces	RS232 Point to Point, RS422 Master – Slave, max. 10 devices
Digital switching outputs.....	Open Drain, 30 VDC, 200 mA
2 Digital outputs for level control ¹⁾	programmable
1 Digital output.....	Device error
Digital input ¹⁾	external triggering
Switching level.....	1-level > +9V...< +30 V, 0-level < 2 V
Mass.....	665 g, 690 g with heating

¹⁾ programmable parameter

Environmental conditions

EMC

- Discharge of static electricity, DIN EN 61000-4-2: 2001
- Immunity to disturbance, DIN EN 61000-6-2: 2001
- Emission, DIN EN 61000-6-4: 2001

Working temperature -10 °C...+50 °C, max. +45 °C in Tracking Mode

Working temperature with heating -40 °C...+50 °C, max. +45 °C in Tracking Mode

Storage temperature -40 °C...+70 °C, dry

Protection class, DIN EN 60529: 1991 ²⁾ IP 65

²⁾ valid with screwed on mating connector and / or screwed together cable gland

Dimension drawing

