



	Model	Range	Features
	RPS-40-5	0.5 - 5"	Compact Size 3.4" x 1.2" x 0.8" 12 - 24VDC Power Input NPN and PNP Outputs, 100mA continuous
	RPS-150-40	2 - 40"	RPS-150 AC or DC Power Input Solid State Relay Outputs N.O./N.C. RPS-150A 20 - 30VDC Power Input Analog Voltage and Analog Current Outputs
	RPS-150-80	5 - 80"	
	RPS-150A-40	2 - 40"	
	RPS-150A-80	5 - 80"	
	RPS-400-6P	2 - 6"	Compact Size 2.0" x 1.5" x 0.7" 20 - 30VDC Power Input NPN Output, 50mA continuous
	RPS-400-30	5 - 30"	22mm Housing 12 - 30VDC Power Input NPN Output 60mA, continuous
	RPS-401-40	4 - 40"	20- 30VDC Power Input 30mm Valox or PVC Housing RPS-401 Solid State Relays N.O./N.C. RPS-401A Analog Voltage and Analog Current Outputs
	RPS-401-80	8 - 80"	
	RPS-401A-40	4 - 40"	
	RPS-401A-80	8 - 80"	
	RPS-401A-80P	8 - 80"	
	RPS-426-80	8 - 80"	20- 30VDC Power Input 30mm Stainless Steel Housing RPS-426 Solid State Relays N.O./N.C. RPS-426A Analog Voltage and Analog Current Outputs
	RPS-426A-80	8 - 80"	





	Model	Range	Features
	RPS-409A-40	4 - 40"	Temperature Compensation
	RPS-409A-80	6 - 80"	Operating Temperature Range -40 - 60°C
	RPS-409A-144	10 - 144"	30mm PVC Housing, IP67
	RPS-409A-40-IS	4 - 40"	Analog 0 - 10V Output
	RPS-409A-80-IS	6 - 80"	RPS-409A
	RPS-409A-144-IS	10 - 144"	20 - 30VDC Power Input
	RPS-409A-216-IS	12 - 216"	RPS-409A-IS
			Intrinsically Safe for use in Hazardous Locations
	RPS-412A-10	3 - 10"	High Accuracy Ultrasonic Sensor
	RPS-412A-16	3 - 16"	±0.002" or 0.05% of Range @ 25°C
	RPS-450-30	5 - 30"	Analog 0 - 10V Output
	RPS-450-72	10 - 72"	Temperature Compensation
	RPS-475-72	10 - 72"	47mm Stainless Steel Housing
			115VAC Power Input
			Zero Crossing Solid State Relay Outputs
			N.O./N.C. 1A maximum
			RPS-450
			30mm Valox Housing
			RPS-475
			30mm Stainless Steel Housing
	RPS-4000	24 - 480"	Long Range Ultrasonic Sensor
			Temperature Compensation
			20 - 30VDC Power Input
			Analog Current Output
	Set Point Controllers		M-1000
	M-1000		Digital Display
	SPC-701		Solid State Relay Outputs 100mA maximum
SPC-704		Analog Voltage or Analog Current Inputs	
			SPC-701/SPC-704
			Form C Relay Output(s) 3A maximum
			Analog Voltage or Analog Current Inputs

